POS (Point of sale) Rolls

TECHNICAL DATA SHEET

DESCRIPTION

POS Thermal Paper rolls are made up from 100% Wood Pulp. It is double coated to give amazing print image at less heat

PRODUCT APPLICATION

This paper roll is used in POS Machine, ATM Machines, Medical Equipment's, and Token Machines.

PHYSICAL PROPERTIES


Paper GSM: Paper GSM: 48/55/72 GSM (According to Customer requirement)


Smoothness: Smooth Surface and 100% Lint free

CONSTRUCTION OF MATERIAL

Item	Unit	48g/m²	55g/m²	72g/m²	Note
Base Weight	g/m2	48±5%	55±5%	72±5%	ISO 536
Caliper	μm	54±5%	60±5%		ISO 534
Brightness	%ISO	≥81	81	81	ISO2470
Smoothness (Bekk)	S	≥250	250	250	ISO 5627
Image Property (Dynamic)	0.28mj/dot 0.42mj/dot	≥90 ≥1.18	≥90 ≥1.18	≥90 ≥1.18	TH-M2/N
Image Property (Static)	70°C 105°C	≤0.20 ≥1.5	≤0.20 ≥1.5	≤0.20 ≥1.5	SWT

STATIC







ASR Universal Ltd

821-299, Roehampton Avenue, Toronto Ontario, Canada M4P1S2

(3) +1 437 988 7611 info@asruniversalltd.com



While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.