

Reinforced Paper WAT

ALL-PURPOSE TAPE

TECHNICAL DATA SHEET

DESCRIPTION

Reinforced Paper tape has a layer of fiberglass which helps in providing extra tensile strength supplemented with water activated adhesive.

PRODUCT APPLICATION

Used for sealing the cartons. Works well on recycled cartons. Recommend using on small, average, and some medium size boxes.

PHYSICAL PROPERTIES:

Caliper 9.8 mils (0.25mm)
CD Tensile 57 lbs/in (250 N/25mm)

ADHESION (WATER AT RECOMMENDED 110°F/43°C):

Figago:

2/0	40
2/1	60
5/0	69
15/0	89

McLaurin: 85

CONSTRUCTION PER 3,000 SQUARE FEET (metric)

Top Ply: 40 lb (65g/m²)
Natural Kraft Paper

Bottom Ply: 40 lb (65g/m²)
Natural Kraft Paper

Laminating Adhesive: High Melt Index
Polypropylene Based
Co-Polymer

Water-Activated Adhesive: Chemically Grafted Starch
Based Copolymer Adhesive,
Designated as S3911

CD Reinforcement (1-1-1) 75 Fiberglass,
0.68" spacing, 25° angle



ASR Universal Ltd
821-299
Roehampton Avenue,
Toronto Ontario,
Canada M4P1S2



+1 437 988 7611



info@asruniversaltd.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

